

WADCO PREFERRED LED LIGHTING REPLACEMENT GUIDE






Image	Description	Wattage (W)	Output (lm)	Optic	Item code	REPLACES
<u>Highbay Lighting</u>						
	TITANIUM COMMERCIAL HIGHBAY 18000LM	150	22300	90°	TTN150C75N-5yr	400W MH
	TITANIUM COMMERCIAL HIGHBAY 27000LM	180	27000	90°	TTN180C75N-5yr	650W MH
	VORTEX COMMERCIAL HIGHBAY 18000LM	170	19600	110°	VOR170C75N-5yr	400W MH
	VORTEX COMMERCIAL HIGHBAY 27000LM	220	27300	110°	VOR240C75N-5yr	650W MH
	VORTEX HEAVY INDUSTRIAL HIGHBAY 19000LM - MINE SPEC- 10yr	170	19000	110°	VOR170C75N -10yr	400W MH
	VORTEX HEAVY INDUSTRIAL INDUSTRIAL HIGHBAY 27000LM - MINE SPEC - 10Yr	220	27000	110°	VOR240C75N- 10Yr	650W MH
	ULTRALED LED HIGHBAY - EMERGENCY OPTIONS AVAILABLE	228	25000	160°	UXL228C75N	650W MH
	ULTRALED LED HIGHBAY - EMERGENCY OPTIONS AVAILABLE	155	19000	160°	UXL155C75N	400W MH
	ULTRALED JUNIOR LED HIGHBAY - EMERGENCY OPTIONS AVAILABLE	228	25000	160°	UXJ228C75N	650W MH
	ULTRALED JUNIOR LED HIGHBAY - EMERGENCY OPTIONS AVAILABLE	155	19000	160°	UXJ1552C75N	400W MH
	CRYSTALUME LED HIGHBAY - EMERGENCY OPTIONS AVAILABLE	228	25000	260°	CRLFLSM-240C5K	650W MH
<u>Lowbay Lighting</u>						
	METROLED - EMERGENCY OPTIONS AVAILABLE	228	25000	160°	MTL228C75N	650W MH
	METROLED - EMERGENCY OPTIONS AVAILABLE	155	19000	160°	MTL155C75N	400W MH
	RONDALED	180	21000	160°	RDL180C75N	400W MH
	METRO VLINE WITH SENSOR - ALSO AVAILABLE IN WALKWAY OPTICS	60	8785	140°	MLV60C75NS	150W MH / 2 X 36W FLOURO
	METRO VLINE - ALSO AVAILABLE IN WALKWAY OPTICS	60	8785		MLV60C75N	150W MH / 2 X 36W FLOURO
	METROLED RECESSED- EMERGENCY OPTIONS AVAILABLE	228	25000	160°	MTLSR228C75N	400W MH

Image	Description	Wattage (W)	Output (lm)	Optic	Item code	REPLACES
	METROLED RECESSED- EMERGENCY OPTIONS AVAILABLE	155	19000	160°	MTLSR155C75N	400W MH
	ULTRALED RECESSED- EMERGENCY OPTIONS AVAILABLE	228	25000	160°	UXR228C75N	650W MH
	ULTRALED RECESSED- EMERGENCY OPTIONS AVAILABLE	155	19000	160°	UXR155C75N	400W MH
	ULTRALED JUNIOR RECESSED- EMERGENCY OPTIONS AVAILABLE	228	25000	160°	UXJR228C75N	650W MH
	ULTRALED JUNIOR RECESSED- EMERGENCY OPTIONS AVAILABLE	155	19000	160°	UXJR155C75N	400W MH
	ALTEC LED BATTEN	56	5200	135°	ALT55S85N	2 X 36W FLOURO
	ALTEC LED BATTEN - EMERGENCY	59	5200	138°	ALT55S85N-ME	2 X 36W FLOURO
<u>Flood Lighting</u>						
	VIPER FLOOD LIGHT 7,600 Lumen - MINE SPEC	70	7600	30°, 60° & 90°	VIP7056SN	400W MH
	ECO15 M2 Stainless Steel	50	7190	90°	ECO1550C75N	150 W MH
	ECO15 50W SS RETRO-FIT KIT	50	7190	90°	ECO1550C5K	150W MH
	PREDATOR FLOOD LIGHT 19,000 Lumen - MINE SPEC	180	19600	30°, 60° & 90°	PRD180S65N	400W MH
	PREDATOR FLOOD LIGHT 28,000 Lumen - MINE SPEC	230	28800	30°, 60° & 90°	PRD220S65N	650W MH
	ECO40 M6 Stainless Steel	230	26000	60°	ECO40230C75N	650W MH
	ECO100 M8 Stainless Steel	480	63400	60°	ECO100480C75N	1000W MH
	OPTIFLOOD 200 PERFORMANCE - HIGHMAST LED FLOOD	200	26000	20°, 30° OR 60°	OPF200C75N30	650W MH
	OPTIFLOOD 400 PERFORMANCE - HIGHMAST LED FLOOD	400	52000	20°, 30° OR 60°	OPF400C75N30	1000W MH

WADCO PREFERRED LED LIGHTING REPLACEMENT GUIDE

Image	Description	Wattage (W)	Output (lm)	Optic	Item code	REPLACES
	OPTIFLOOD 600 PERFORMANCE - HIGHMAST LED FLOOD	600	78000	20°, 30° OR 60°	OPF600C75N30	1300W MH
	OPTIFLOOD 800 PERFORMANCE - HIGHMAST LED FLOOD	800	104000	20°, 30° OR 60°	OPF800C75N30	1600W MH
	OPTIFLOOD 1200 PERFORMANCE - HIGHMAST LED FLOOD	1200	156000	20°, 30° OR 60°	OPF1200C75N30	2000W MH
	AL60 1500W ASYMETRICAL FLOOD 415V 60° - Mine Spec - Complete with Braided Cable, Cable Protector Plate and Wireless Capabilities. Also available in 240V	1500	164000	60°	AL1500S60	2000W - 3000W MH
	AL90 1500W ASYMETRICAL FLOOD 415V 90° - Mine Spec - Complete with Braided Cable, Cable Protector Plate and Wireless Capabilities. Also available in 240V	1500	164000	90°	AL1500S90	2000W - 3000W MH
	AL180 1500W ASYMETRICAL FLOOD 415V 180° - Mine Spec - Complete with Braided Cable, Cable Protector Plate and Wireless Capabilities. Also available in 240V	1500	164000	180°	AL1500S180	2000W - 3000W MH
	AL SERIES ASYMETRICAL LIGHT SPILL SHEILD (INDIVIDUAL SHEILD)				ALLSS	
<u>Stairway Lighting</u>						
<u>Key Hole Mount</u>						
	PRISMLED 30W SS KH CUT-OFF FITTING	30	4430	120°	PMS30C5	70W MH/HPS
	PRISMLED 32W SS KH AUX MAINTAINED CUT-OFF FITTING	32	4430	120°	PMS32C5A	70W MH/HPS EMERGENCY
	PRISMLED 30W SS KEY HOLE DIFFUSED FITTING	30	3560	160°	PMSD30C5	70 W MH/HPS
	PRISMLED 32W SS KEY HOLE AUX MAINTAINED DIFFUSED FITTING	32	3560	160°	PMSD32C5A	70W MH/HPS
	OPTILED 50W SS KH DIFFUSED FITTING	50	7190	180°	OPS50C5	150W MH/HPS
<u>Retrofit Kits</u>						
	PRISMLED 30W SS RETRO-FIT KIT	30	4450	120°	PMS30C5K	RETROFITS PRISIMLUX FITTINGS
	PRISMLED 32W SS AUX MAINTAINED RETRO-FIT KIT	32	4450	120°	PMS30C5AK	RETROFITS PRISIMLUX FITTINGS
	OPTILED 30W RETRO-FIT KIT	50	7190	120°	OPS50C5K	RETROFITS OPTLUX FITTINGS
<u>Spare Diffuser Assembly</u>						
	PRISMLED SS DIFFUSER ASSEMBLY				PMS-DA	







WADCO PREFERRED LED LIGHTING REPLACEMENT GUIDE

Image	Description	Wattage (W)	Output (lm)	Optic	Item code	REPLACES
	PRISMILED SS GLASS ASSEMBLY				PMS-GA	
	OPTILED SS DIFFUSER ASSEMBLY				OPS-DA	
<u>Accessories</u>						
	PRISMILED / OPTILED - AMBER TURTLE KIT				PMS/OPL-AMBERKIT	
<u>Conveyor / Walkway Lighting</u>						
<u>Aluminium Pole Mount</u>						
	VECT-R CONVEYOR WALKWAY FITTING -12MTR SPACINGS	34	7400	Eliptical	VRPC34S5	120W MH EMERGENCY
	VECT-R MAINTAINED EMERGENCY CONVEYOR WALKWAY FITTING -12MTR SPACINGS	38	7400	Eliptical	VRPC38S5	120W MH EMERGENCY
	VECT-R CONVEYOR WALKWAY FITTING -18MTR SPACINGS	55	7400	Eliptical	VRPC55S5	150W MH EMERGENCY
	VECT-R MAINTAINED EMERGENCY CONVEYOR WALKWAY FITTING -18MTR SPACINGS	59	7400	Eliptical	VRPC59S5	150W MH EMERGENCY
<u>Cast Pole Mount</u>						
	HANDILED 30W SS PM CUT-OFF FITTING	30	2750	Eliptical	HLPC30S5	70W MH
	HANDILED 32W SS PM AUX MAINTAINED CUT-OFF FITTING C/W REMOTE SS CONTROL GEAR BOX	32	2750	Eliptical	HLPC32S5A	70W MH EMERGENCY
	HANDILED 30W SS PM DIFFUSED FITTING	30	2750	Eliptical	HLPCD30S5	70W MH
	HANDILED 32W SS PM AUX MAINTAINED DIFFUSED FITTING C/W REMOTE SS CONTROL GEAR BOX	32	2750	Eliptical	HLPCD32S5A	70W MH EMERGENCY
<u>Stainless Steel Pole Mount</u>						
	HANDILED 30W SS PM CUT-OFF FITTING	30	2750	Eliptical	HLPS30S5	70W MH
	HANDILED 32W SS PM AUX MAINTAINED CUT-OFF FITTING C/W REMOTE SS CONTROL GEAR BOX	32	2750	Eliptical	HLPS32S5A	70 W MH/HPS EMERGENCY
	HANDILED 30W SS PM DIFFUSED FITTING	30	2750	Eliptical	HLPSD30S5	70 W MH
	HANDILED 32W SS PM AUX MAINTAINED DIFFUSED FITTING C/W REMOTE SS CONTROL GEAR BOX	32	2750	Eliptical	HLPSD32S5A	70 W MH/HPS EMERGENCY



WADCO PREFERRED LED LIGHTING REPLACEMENT GUIDE

Image	Description	Wattage (W)	Output (lm)	Optic	Item code	REPLACES
	INDILED 40W SS PM CUT-OFF FITTING	40	3393	Eliptical	INLP40S5	120 W MH/HPS
	INDILED 42W SS PM AUX MAINTAINED CUT-OFF FITTING	42	3393	Eliptical	INLP32S5A	120W MH/HPS EMERGENCY
<u>Key Hole Mount</u>						
	HANDILED 30W SS KEY HOLE CUT-OFF FITTING	30	2750	Eliptical	HLKS30S5	70 W MH/HPS
	HANDILED 32W SS KEY HOLE AUX MAINTAINED CUT-OFF FITTING C/W REMOTE SS CONTROL GEAR BOX	32	2750	Eliptical	HLKS32S5A	70 W MH/HPS EMERGENCY
	HANDILED 30W SS KEY HOLE DIFFUSED FITTING	30	2750	Eliptical	HLKSD30S5	70 W MH/HPS
	HANDILED 32W SS KEY HOLE AUX MAINTAINED DIFFUSED FITTING C/W REMOTE SS CONTROL GEAR BOX	32	2750	Eliptical	HLKSD32S5A	70 W MH/HPS EMERGENCY
	INDILED 40W SS KH FITTING	40	3393	Eliptical	INLK40S5	120W MH/HPS
	INDILED 42W SS KH AUX MAINTAINED FITTING	42	3393	Eliptical	INLK42S5A	120W MH/HPS EMERGENCY
	INDILED 4W SS EMERGENCY EXIT	4			INSL-EXIT-S	EMERGENCY EXIT LIGHT
<u>Conveyor / Walkway Lighting</u>						
<u>Retrofit Kits</u>						
	HANDILED 30W SS RETRO-FIT KIT	30	2750	Eliptical	HLS30S5K	RETROFITS HANDILUX FITTINGS
	HANDILED 32W SS AUX MAINTAINED RETRO-FIT KIT LESS DRIVE AND EMERGENCY CONTROL GEAR	32	2750	Eliptical	HLS32S5AK	RETROFITS HANDILUX EMERGENCY FITTINGS
	INDILED 40W RETRO-FIT KIT	40	3393	Eliptical	INL40S5K	RETROFITS INDILUX FITTINGS
	INDILED 5W AUX NON-MAINTAINED RETRO-FIT KIT LESS DRIVER	5	600		INL5S5AS001	
	INDILED 42W AUX MAINTAINED RETRO-FIT KIT	44	3393	Eliptical	INL44S5AK	RETROFITS INDILUX EMERGENCY FITTINGS
<u>Accessories</u>						
	HANDILED / INDILED - AMBER TURTLE KIT				HLN/INL-AMBERKIT	TURTLE FRIENDLY 70W HPS







WADCO PREFERRED LED LIGHTING REPLACEMENT GUIDE

Image	Description	Wattage (W)	Output (lm)	Optic	Item code	REPLACES
<u>Spare Diffuser Assembly</u>						
	HANDILED SS DIFFUSER ASSEMBLY				HLS-DA	
	HANDILED SS GLASS ASSEMBLY				HLS-GA	
	HANDILED CAST DIFFUSER ASSEMBLY				HLC-DA	
	HANDILED CAST GLASS ASSEMBLY				HLC-GA	
<u>BOSSE' INDUSTRIAL RANGE</u>						
<u>Bulkhead</u>						
	BOSSE' INDUSTRIAL BULKHEAD 34w LED AREA	34	2750	50°x50°	WBB34SC50	70W MH
	BOSSE' INDUSTRIAL BULKHEAD 34w LED AREA - EMERGENCY	37	2750	50°x50°	WBB37SC50ME	70W MH EMERGENCY
	BOSSE' INDUSTRIAL BULKHEAD 34w LED WALKWAY	34	2750	60°x25°	WBB34SE62	70W MH
	BOSSE' INDUSTRIAL BULKHEAD 34w LED WALKWAY-EMERGENCY	37	2750	60°x25°	WBB37SE62ME	70W MH EMERGENCY
<u>Linear</u>						
	BOSSE' INDUSTRIAL LINEAR 34w LED, White-Light	34	3400	Elliptical	WBL34S	70W MH / 2 X 18W
	BOSSE' INDUSTRIAL LINEAR 34w LED, White-Light - EMERGENCY	37	3400	Elliptical	WBL37SME	70W MH / 2 X 18W EMERGENCY
	BOSSE' INDUSTRIAL LINEAR 68W LED, White-Light	68	6800	Elliptical	WBL68S	150W MH / 2 X 36W EMERGENCY
	BOSSE' INDUSTRIAL LINEAR 68W LED, White-Light - EMERGENCY	71	6800	Elliptical	WBL71SME	150W MH / 2 X 36W EMERGENCY
<u>Safety Shower Linear</u>						
	BOSSE' INDUSTRIAL SAFETY SHOWER LINEAR, 34w GREEN LED - EMERGENCY	37	519(NM)	Elliptical	WBL34SGME	EYE WASH STATION LIGHT
<u>BOSSE' HAZARDOUS RANGE</u>						
<u>Bulkhead</u>						
	BOSSE' HAZARDOUS BULKHEAD 34w LED AREA	34	2500	50°x50°	WBB34SC50-Z1	70W MH
	BOSSE' HAZARDOUS BULKHEAD 34w LED AREA - EMERGENCY	37	2500	50°x50°	WBB34SC50ME-Z1	70W MH EMERGENCY
	BOSSE' HAZARDOUS BULKHEAD 34w LED WALKWAY	34	2500	60°x25°	WBB34SE62-Z1	70W MH

WADCO PREFERRED LED LIGHTING REPLACEMENT GUIDE

Image	Description	Wattage (W)	Output (lm)	Optic	Item code	REPLACES
	BOSSE' HAZARDOUS BULKHEAD 34w LED WALKWAY-EMERGENCY	37	2500	60°x25°	WBB34SE62ME-Z1	70W MH EMERGENCY
<u>Linear</u>						
	BOSSE' HAZARDOUS ZONE 1 LINEAR 34w LED, White-Light	34	2500	Elliptical	WBL34S-Z1	70W MH / 2 X 36W
	BOSSE' HAZARDOUS ZONE 1 LINEAR 34w LED, White-Light - EMERGENCY	37	2500	Elliptical	WBL37SME-Z1	70W MH / 2 X 36W EMERGENCY
	BOSSE' HAZARDOUS ZONE 1 LINEAR 68W LED, White-Light	68	5000	Elliptical	WBL68S-Z1	150W MH / 2 X 36W
	BOSSE' HAZARDOUS ZONE 1 LINEAR 68W LED, White-Light - EMERGENCY	71	5000	Elliptical	WBL71SME-Z1	150W MH / 2 X 36W EMERGENCY
	BOSSE' HAZARDOUS ZONE 2 LINEAR 34w LED, White-Light	34	3400	Elliptical	WBL34S-Z2	70W MH / 2 X 36W
	BOSSE' HAZARDOUS ZONE 2 LINEAR 34w LED, White-Light - EMERGENCY	37	3400	Elliptical	WBL37SME-Z2	70W MH / 2 X 36W EMERGENCY
	BOSSE' HAZARDOUS ZONE 2 LINEAR 68W LED, White-Light	68	6800	Elliptical	WBL68S-Z2	150W MH / 2 X 36W
	BOSSE' HAZARDOUS ZONE 2 LINEAR 68W LED, White-Light - EMERGENCY	71	6800	Elliptical	WBL71SME-Z2	150W MH / 2 X 36W EMERGENCY
<u>Safety Shower Linear</u>						
	BOSSE' HAZARDOUS ZONE 1 SAFETY SHOWER LINEAR, 34w GREEN LED - EMERGENCY	37	519(NM)	Elliptical	WBL34SGME-Z1	
<u>Street Lighting</u>						
	ECO20 STREETLIGHT	30			ECO2030C5N	70W MH
	ECO20 STREETLIGHT	60			ECO2060C5N	150W MH
	STEALTH 150W STREETLIGHT- TYPE 3 OPTIC	150	19200		STL150S64N	400W MH
	STEALTH 240W STREETLIGHT- TYPE 3 OPTIC	250	30000		STL240S64N	650W MH
<u>Accessories</u>						
	Straight Stanchion Mount, 34OD for BOSSE' Bulkhead				WBB-SMS-34OD	34 OD STANCHION MOUNT FOR BULKHEAD
	Emergency Exit sign KIT for BOSSE' Bulkhead				WBB-EMEX-RM	EMERGENCY EXIT MOUNT FOR BULKHEAD

WADCO PREFERRED LED LIGHTING REPLACEMENT GUIDE

Image	Description	Wattage (W)	Output (lm)	Optic	Item code	REPLACES
	Lens kit for BOSSE' Bulkhead - (MUST BE ADDED AT ORDER)				WBB-LENSKIT	LENS KIT BULKHEAD
	Flush Mounting Kit, Stainless Steel for BOSSE' Bulkhead				WBB-CM-SS	
	Flush Mounting Kit, Stainless Steel for BOSSE' Linear				WBL-CM-SS	
	BOSSE' Linear Pole Clamp Kit 38-41mm Diameter, Stainless Steel				WBL-PC38-SS	
	BOSSE' Linear Pole Clamp Kit 59-62mm Diameter, Stainless Steel				WBL-PC59-SS	
	Adjustable Swivel Bracket Mounting Kit, Stainless Steel for BOSSE' Linear				WBL-ADJSB-SS	
UPDATED JA 9/10/17	ANY ENQUIRES - PLEASE CONTACT: JASON ATKINS - WADCO LIGHTING - 0401 230 202 / jason.atkins@gmi.net.au					